

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9624)

-----  
At point of intersection (7.36 chs. N.0°45'W. of the cor. of secs. 1 & 12 only T26-1W) Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for the closing cor. of secs. 6 & 7, with brass cap marked:

T26S		T26S	
S 1		$\frac{S\ 6}{S\ 7}$	CC
R1W		R1E	
		1928	

from which

- A Fir 36" dia., bears N.20°E., 58 lks. dist. mkd. T26S R1E S6 CC BT.
- A Fir 40" dia., bears S.18°E., 90 lks. dist. mkd. T26S R1E S7 CC BT.