

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100633

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 1 only; T26-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4076)

Set a basalt stone 12x10x6 ins., 8" in the ground for ¼ sec. cor., marked ¼ on W. face, from which

A Cedar 24" dia., bears S.66°E., 67 lks. dist. mkd. ¼ S6 BT.

A Cedar 20" dia., bears N.58°W., 83 lks. dist. mkd. ¼ S1 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9530-31)

Intersect the old ¼ sec. cor., established for secs. 1 and 6, which is a basalt stone 8x6x4 ins. above ground marked ¼ on W. face. I change this cor. to refer to sec. 1 only, obliterating the scribe marks on the old SE. BT. Alongside of old stone cor., SET an iron post 3 ft. long, 1" dia., 27" in the ground, for the ¼ sec. cor. of sec. 1 only, with brass cap marked: ¼ S1|

1928

from which

A Cedar 26" dia., bears S.66°E., 67 lks. dist. mkd. ¼ S6 BT. (Old BT)

A Cedar 22" dia., bears S.35°W., 63 lks. dist. mkd. ¼ S1 BT.

A Cedar 22" dia., bears N.58°W., 83 lks. dist. mkd. ¼ S1 BT. (Old BT)