

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 6; T27-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9868)  
-----  
Set an iron post, 3 ft. long, 1" dia., 4" in the ground to bedrock, supported in a mound of stone, for ¼ sec. cor., with brass cap marked  
$$\frac{1}{4} \frac{S \ 31}{S \ 6}$$
  
1927  
from which  
A fir, 14" dia., bears N.8°E., 11 lks., mkd: ¼ S31 BT.  
A fir, 14" dia., bears S.53°W., 32 lks., mkd: ¼ S6 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 29, 1969 - C.S. File 54/94-22  
-----  
Found - 1927 GL0 Brass Cap, properly marked but out of ground.  
Reset - Brass Cap at ¼ corner in Mound of Stone.  
14" D.Fir, now down, N.8°E. 7.3 ft., opened for scribe.  
14" D.Fir, now dead, S.53°W. 21.1 ft., scribe visible.  
New BTs- 10" D.Fir N.87°W. 19.1 ft., scribed: "¼ S31 CS BT".  
7" D.Fir S.30°W. 8.8 ft., scribed "¼ S 6 CS BT".  
This corner lies about 15 ft. south of high ridge.  
NW BT is on top of said ridge.