

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Cor. Secs. 31, 32; 5 & 6 T27-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9867)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd

T26S R1E  
S 31 | S 32  
S 6 | S 5  
1927  
T27S

from which

- A fir, 48" dia., bears N.20°E., 42 lks., mkd: T26S R1E S32 BT.
- A fir, 10" dia., bears S.9°E., 24 lks., mkd: T27S R1E S5 BT.
- A fir, 36" dia., bears S.51°W., 51 lks., mkd: T27S R1E S6 BT.
- A fir, 18" dia., bears N.87°W., 133 lks., mkd: T26S R1E S31 BT.