

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9610)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T26S R1E  
S 19 | S 20  
S 30 | S 29  
1928

from which

- A pine, 20" dia., bears N.8°E., 45 lks., mkd: T26S R1E S20 BT.
- A hemlock, 22" dia., bears S.25°W., 97 lks., mkd: T26S R1E S29 BT.
- A fir, 24" dia., bears S.8°W., 77 lks., mkd: T26S R1E S30 BT.
- A hemlock, 14" dia., bears N.58°W., 100 lks., mkd: T26S R1E S19 BT.