

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9617-8)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T26S R1E  
S 7|S 8  
S 18|S 17  
1928

from which

- A fir, 10" dia., bears N.39°E., 101 lks., mkd: T26S R1E S8  
BT.
- A fir, 8" dia., bears S.68°E., 49 lks., mkd: T26S R1E S17  
BT.
- A fir, 14" dia., bears S.24°W., 70 lks., mkd: T26S R1E S18  
BT.
- A fir, 6" dia., bears N.62°W., 56 lks., mkd: T26S R1E S7  
BT.