

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Cor. Secs 5, 6; 31 & 32 T25½-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9547-8)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd

T25½S R1E  
S 31|S 32  
S 6|S 5  
T26S  
1928

from which

- A fir, 30" dia., bears N.12°E., 188 lks., mkd: T25½S R1E S32 BT.
- A fir, 16" dia., bears S.70°E., 33 lks., mkd: T26S R1E S5 BT.
- A fir, 8" dia., bears S.49°W., 25 lks., mkd: T26S R1E S6 BT.
- A cedar, 12" dia., bears N.12°W., 26 lks., mkd: T25½S R1E S31 BT.

FD. by ODOT 10/2007, St. Hwy 138-011Y

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 2/26/26 - C.S. File 67/62-18

-----  
Found - 3¼" GLO brass cap proj. 6".

T25½S R1E  
S 31|S 32  
S 6|S 5  
T26S  
1928

31" G. Fir S.59°W. 16.5 ft. (Rec. S.49°W.) Fully healed single blaze.

6" x ½ ft. rotted cedar stub N.12°W. 17.2 ft.

NGS monument STEAM S.82¾°W. 416.9 ft. 3½" brass cap under metal cover. 8" below parking lot surface.

New - 21" Grand Fir S.11°E. 17.8 ft. 3½" mag nail right side center  
44" red cedar N.11°W. 93.0 ft. 3½" mag nail right side center

Notes - Mon. is on flat flood plain bench approx. 40 ft. south of paved access road.

Compass decl. 14¾°E.

TRIMBLE GEO XT POSITION

43°.203679177 N. 122°.441364486 E.