

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9599-9600)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T26S R1E  
S 8 | S 9  
S 17 | S 16  
1928

from which

- A pine, 16" dia., bears N.42°E., 142 lks., mkd: T26S R1E S9 BT.
- A hemlock, 30" dia., bears S.46°E., 86 lks., mkd: T26S R1E S16 BT.
- A fir, 12" dia., bears S.45°W., 26 lks., mkd: T26S R1E S17 BT.
- A hemlock, 12" dia., bears N.25°W., 77 lks., mkd: T26S R1E S8 BT.