

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9585-6)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T26S R1E  
S 9 | S 10  
S 16 | S 15  
1928

from which

- A cedar, 16" dia., bears N.36°E., 125 lks., mkd: T26S R1E S10 BT.
- A fir, 8" dia., bears S.50°E., 133 lks., mkd: T26S R1E S15 BT.
- A fir, 10" dia., bears S.71°W., 85 lks., mkd: T26S R1E S16 BT.
- A fir, 8" dia., bears N.53°W., 137 lks., mkd: T26S R1E S9 BT.