

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9564)

-----

Set an iron post, 3 ft. long, 2" dia., 18" in the ground to bedrock, supported by a mound of stone, with a 4 ft. base, 1 ft. high, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd

T26S	R1E
<u>S 27</u>	<u>S 26</u>
S 34	S 35
1928	

from which

- A fir, 40" dia., bears N.23°E., 27 lks., mkd: T26S R1E S26  
BT.
- A fir, 30" dia., bears S.26°E., 8 lks., mkd: T26S R1E S35  
BT.
- A fir, 30" dia., bears S.44°W., 83 lks., mkd: T26S R1E S34  
BT.
- A fir, 30" dia., bears N.42°W., 56 lks., mkd: T26S R1E S27  
BT.