

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9560)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 11|S 12  
1928

from which

- A fir, 8" dia., bears S.29°E., 58 lks., mkd: 1/4 S12 BT.
- A fir, 10" dia., bears N.35°W., 15 lks., mkd: 1/4 S11 BT.

John Ransom, USFS - Done by: Hillman - 1/2015 - C.S. File 65/89-23

-----  
Found - A 2 1/2" dia., brass cap on a 1" dia., galvanized iron pipe projecting 12" above the ground, loose and leaning. (properly mkd) **I straightened and fortified** the monument such that it is firm and projecting 9" above the ground.

No BTs or other accessories fd.

- New -
- 18" D.Fir brs. N.34 1/2°W., 6.2 ft., mkd "1/4S11" "BT" on a double blaze.
  - 24" D.Fir brs. S.72°E., 17.9 ft. mkd "1/4S12" "BT" on a double blaze.
  - 16" D.Fir brs. S.15 1/2°W., 16.9 ft. mkd "X" "BT" on a double blaze.

Placed an alum. guard post with monument sign 2 ft. south of the monument.

Note - Follow Forest Road 4713-100 to the junction with 4713-120. Walk NW on Road 4713-100 about 115 ft. The corner is West 345 ft. on a west facing slope.

Measurements made with staff compass (15 3/4°E decl.) and a steel tape.