

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 35 & 36 T25½-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9542)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T25½S R1E  
S 35|S 36  
S 2|S 1  
T26S  
1928

from which

- A fir, 7" dia., bears N.58°E., 47 lks., mkd: T25½S R1E S36  
BT.
- A fir, 7" dia., bears S.9°E., 14 lks., mkd: T26S R1E S1  
BT.
- A fir, 12" dia., bears S.21°W., 32 lks., mkd: T26S R1E S2  
BT.
- A fir, 8" dia., bears N.77°W., 27 lks., mkd: T25½S R1E S35  
BT.