

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Township corner

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9861)

-----

Set an iron post, 3 ft. long, 3" in dia., 27" in the ground, for the cor. of Tps. 26 & 27 S., Rs. 1 & 2 E, with brass cap marked:

T26S	
R1E	R2E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
1927	
T27S	

from which

- A fir, 10" dia., bears N.25°E., 55 lks., mkd: T26S R2E S31 BT.
- A fir, 16" dia., bears S.48°E., 81 lks., mkd: T27S R2E S6 BT.
- A fir, 10" dia., bears S.45°W., 66 lks., mkd: T27S R1E S1 BT.
- A fir, 34" dia., bears N.39°W., 8 lks., mkd: T26S R1E S36 BT.