

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T26-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9539)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T26S	
R1E	R2E
S 1	S 6
S 12	S 7
1928	

from which

- A fir, 4" dia., bears N.54°E., 27 lks., mkd: T26S R2E S6  
BT.
- A fir, 16" dia., bears S.30°E., 56 lks., mkd: T26S R2E S7  
BT.
- A fir, 12" dia., bears S.67°W., 51 lks., mkd: T26S R1E S12  
BT.
- A fir, 4" dia., bears N.83°W., 18 lks., mkd: T26S R1E S1  
BT.