

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION CC Tps 26 & 27 S., R1W (SW Cor. S31)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer S. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4786)

I establish a closing cor. for Tps. 26 and 27 S., R. 1 W. at the point of intersection (14.50 chs. S. of the cor. of Tps. 26 & 27 S., Rs. 1 & 2 W.) of the random line with the West bdy. as follows:

Set a basalt stone 15x12x8 ins., 10" in ground for closing cor. of Tps. 26 and 27 S., R 1 W., marked with CC on W. and with 6 notches on N., E., and S. edges, from which

A Fir 12" dia., bears N.80°E., 39 lks. dist. mkd. T26S R1W S31 BT.

A Cedar 28" dia., bears S.62°E., 32 lks. dist. mkd. T27S R1W S6 BT.

(I destroy all marks on the old Tp. cor. referring to Tps. 26 and 27 S., R. 1 W. (ID #100114))

Fd. and tied in GLO Survey by Fred Mensch, U.S. Surveyor under Contract #797, April 19, 1910 - (DCSO records Vol. 10 Page(s) 4092)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1967 - C.S. File 54/40-51

Found - Corner stone mkd. "CC" and 6 notches on N. & S. edges.

Orig. 28" now 38" Cedar S.62°E., 21.1 ft. alive, scribe visible on unhealed blaze. Rescribe "T27S R1W S6 CC CS BT"

Orig. 12" now 22' W.Fir N.80°E., 25.7 ft. alive, scribe visible on unhealed blaze. Rescribe "T26S R1W S31 CC CS BT"

Set Brass cap at cor. mkd: County Surveyors Office
T26S R2W CC | S 31 R1W
T27S | S 6
1967

New BT - 14" W.Fir S.35°E., 30.9 ft. mkd. T27S R1W S6 CC CS BT.

This corner lies on steep N. slope approx. 450 ft. S. of E. Mile Creek.