

PRIMARY CORNER DESCRIPTION SE Cor. for Sec. 36, T26-2

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 10 Page(s) 4186)

-----

Set a Chinquapin post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 31 and 36 and marked T26S S31 on NE.; R1W S6 on SE.; T27S S1 on SW.; R2W S36 on NW. faces, with 6 notches on N., S., E., and W. edges, from which

    A Laurel 7" dia., bears N.45°E., 28 lks. dist. mkd. T26S R1W S31 BT.

    A Fir 6" dia., bears S.60°E., 31 lks. dist. mkd. T27S R1W S31 BT.

    A Fir 40" dia., bears S.74°W., 25 lks. dist. mkd. T27S R2W S1 BT.

    A Fir 24" dia., bears N.3°W., 23 lks. dist. mkd. T26S R2W S36 BT.

Fd. and used corner in GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4868-69)

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4785)

-----

The Cor. of Tps. 26 and 27 S., Rs. 1 and 2 W., which is a post greatly decayed and witnessed as described by the Surveyor General.

In the place of the decayed stake, I set a basalt stone 15x12x8 ins., 10" in the ground for cor., marked with 6 notches on each edge.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1967 - C.S. File 54/40-52

-----

Found - No trace of original corner stone or other obliterated BT.

    Orig. 40" now 48" Fir, down, S.74°W., 16.5 ft., open and shows scribe.

    Orig. 24" now down and almost completely buried Fir, N.3°W., 15.2 ft.

    Orig. 6" now 16" Fir, down, S.60°E., 20.5 ft., open and find obliterated blaze as called for.

Set Brass cap at cor. mkd:           County Surveyors Office

T26S		S 36	
T27S	R2W	S 1	R1W

1967

(Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100114

PRIMARY CORNER DESCRIPTION SE Cor. for Sec. 36, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 10" Cedar N.70°W., 36.5 ft. mkd. T26S R2W S36 CSBT  
18" D.Fir S.88°W., 41.7 ft. mkd. T27S R2W S1 CS BT.  
Corner lies on southerly slope.

Fd. BC & 2 BTs by D. Edwards, 3/2008 - M155-16