

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 and 36 only, T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4063-64)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for corner to secs. 25, 30, 31 and 36, marked T26S S30 on NE.; R1W S31 on SE.; R2W S36 on SW. and S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which
A Fir 36" dia., bears N.40°E., 63 lks. dist. mkd. T26S R1W S30 BT.
A Fir 48" dia., bears S.10°E., 23 lks. dist. mkd. T26S R1W S31 BT.
A Fir 24" dia., bears S.40°W., 31 lks. dist. mkd. T26S R2W S36 BT.
A Cedar 48" dia., bears N.40°W., 18 lks. dist. mk.d T26S R2W S25 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4088-89)

The cor. of secs. 25, 30, 31 and 36, which is a decayed post, marked and witnessed as described by the surveyor general, bears E. 4.08 chs. dist.
I re-establish the cor. in its original position as the cor. of secs. 35 and 36, T26S R2W, only as follows:
Set a basalt stone 15x10x8 ins., 10" in the ground for cor. of secs. 25 and 36, T26S R2W marked with 5 notches on N. and 1 notch on S. edge, from which
A Fir 24" dia., bears S.40°W., 31 lks. dist. mkd. T26S R2W S36 BT.
A Cedar 48" dia., bears N.40°W., 18 lks. dist. mkd. T26S R2W S25 BT.
I obliterate marks on former bearing trees referring to T26S R1W.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4281)

Intersect the original McQuinn cor. established in 1883 as the cor. of secs. 25, 30, 31 and 36 and reestablished in 1910 by Deputy Mensch as the cor. of secs. 25 and 36 only, which is a basalt stone, 15x10x8 ins., firmly set, marked and witnessed as described by the surveyor general. I now remove the old stone (set by Deputy Mensch in place of the original cor., a post) and in its place, SET an iron post 3 ft. long,
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 and 36 only, T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

3" dia., 24" in the ground for cor. of secs. 25 and 36, with
brass cap mkd.

T26S
S25
S36
R2W

1916

from which

A Fir 30" dia., bears S.40°W., 31 lks. mkd T26S R2W S36 BT

A Cedar 48" dia. bears N.40°W., 18 lks mkd T26S R2W S25 BT

I destroy the corresponding cor. of the rejected revision
survey and marks on bearing trees.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Aug. 10, 1967 - C.S. File 54/40-44

Found - 1916 GLO brass cap, firmly set, properly marked.
Orig. 30" now 32" Fir stump, S.40°W., 20.5 ft.,
shows scar.
Orig. 48" now 50" Cedar, down, N.40°W., 11.9 ft.,
shows scribe marks on rotted face.

New BTs- 50" Cedar S.84°W., 23.4 ft. mkd. T26S R2W S36 CSBT
36" D.Fir N.76°W., 37.1 ft. mkd. T26S R2W S25 CSBT
Corner lies on top of spur, sloping SW. at old cutting
corner. Cut off in section 36.

Don Bentz - For: US Forest Service - 7/19/1993 - C.S.
63/153-12

Found - 3" Iron pipe 12" above ground in a 24" mound of
stone with a 3" brass cap properly marked.
40" Cedar bears S.84°W., 23.4 ft. with a partly
visible scribing.
28" D.Fir with healed blaze was blown over.

New BT - 20" D.Fir with double blaze, upper scribed T26S R2W
S25, lower blaze scribed BT with nail and washer
stamped LS839 bears N.78°W., 42.8 ft.

All BTs have a 6" red band painted around the tree and the
blaze face painted red. USFS sign 54-3 "Bearing Tree" and
54-9 "Land Surveying Monument" are nailed to all BTs.

David Edwards - For: Seneca Jones Timber Co. - 10/2015 -
M169-80

Found - 1916 GLO brass cap
1967 DCS BT A 40" Cedar bears S84°W., 23.4 ft.
1967 DCS BT A 27" Fir bears N.78°W., 42.8 ft.
All with healed blazes.

Set - 6 ft. steel post 2 ft. east. _____