

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4155-56)

The length of the W. bdy. of sec. 30 is 80.08 chs. Therefore at point midway on this line (6.60 chs. N.1°20' of the ¼ sec. cor. on E. bdy. of sec. 25, T26S R2W) I establish ¼ sec. cor. on W. bdy. of sec. 30 as follows:

Set a basalt stone 15x12x10 ins., 10" in the ground for ¼ sec. cor. on W. bdy. of sec. 30, marked ¼ on E. face, from which

A Cedar 30" dia., bears N.3½°E., 38 lks. dist. mkd. ¼ S30 BT.

A Cedar 30" dia., bears S.29°E., 55 lks. dist. mkd. ¼ S30 BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4283)

At a point from which the ¼ cor. of sec. 30, (established by Deputy Mensch in 1910 which is a basalt stone 15x12x10 ins., firmly set, marked and witnessed as described by the surveyor general) bears N.89°42'W., 52 lks. dist.

To this point, I now move the original corner stone, which I set 10" in the ground, for ¼ cor. of sec. 30, marked ¼ on E. face; from which

A Cedar 18" dia., bears N.49°E., 25 lks. dist. mkd. ¼ S30 BT.

A Cedar 14" dia., bears S.60°E., 55 lks. dist. mkd. ¼ S30 BT.

I now destroy marks on bearing trees at former cor.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 19, 1966 - C.S. File 52/77-14

Found - Orig. 18" now 20" Cedar N.49°E., 16.5 ft., alive and shows old "¼ S30 BT" scribe on unhealed blaze.

No trace of SE. BT due to cat logging.

No trace of stone called for.

Set Brass cap at cor. mkd: County Surveyors Office

T 26 S

R 2 W | ¼ S30 R1W

1966

New BTs- 28" D.Fir S.27½°E., 66.7 ft. mkd. ¼ S30 CS BT.

8" Hemlock S.77°E., 94.5 ft. mkd. ¼ S30 CS BT.

This corner lies approx. 60 ft. S. of Thunder Mt. Road.

cont.

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 3/25/2024
- C.S. File 67/57-43

Found - 2½" DCSO brass cap (properly mkd)
38" Cedar N.49°E., 16.5 ft. good scar, add 3½" mag
nail right side center.
39" D.Fir S.27½°E., 66.7 ft. good scar, add 3½" mag
nail right side center.
24" Hemlock S.77°E., 94.5 ft. good scar, add 3½" mag
nail right side center.

Note - Compass decl. 14½°E.
(Area Burnt 9/2020)

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N. 162228.222 E. 286732.832