

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4065)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner marked ¼ S on W. face, from which
A Fir 10" dia., bears N.20°E., 33 lks. dist. mkd. ¼ S BT
A Fir 5" dia., bears S.19½°W., 17 lks. dist. mkd. ¼ S BT

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4088 and 4090-91)

(Page 4088)
The ¼ sec. cor. is not found after careful search. Set temp. ¼ sec. cor.
(Pages 4090-91)
Edge of bluff 100 ft. high, point for ¼ sec.cor. will fall on bluff.
(43.25 chs.)
A basalt stone 8x8x12 ft. for WITNESS cor. to the ¼ sec. cor. on E. bdy. of sec. 24, T26S R2W, I mark with a cross (X) at exact cor. point "W C ¼" W. of cross, from which
A Fir 6" dia., bears S.13°W., 14 lks. dist. mkd. WC ¼ S24 BT.
A Cedar 10" dia., bears N.77°W., 14 lks. dist. mkd. WC ¼ S24 BT.
(N.1°20'W, 43.80 chs. - Point for ¼ sec. cor. on bluff.)

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4285-86)

(45.70½ chs.)
True point (midpoint bet. McQuinn Cors.) for ¼ cor. of sec. 24 falls on bluff where a permanent cor. cannot be established, therefore at
(46.31 chs., foot of bluff)
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for witness cor. to the ¼ cor. of sec. 24, with brass cap marked:
¼
S 24
WC
1916
from which
A protruding point of bluff (basalt rock) bears S.51°W., 6 lks. dist. mkd. B O ¼ S24 WC with cross (X) at exact bearing point. (Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100341

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 48" dia., bears N.6°W., 54 lks. dist. mkd. WC ¼ S24 BT.

I destroy the corresponding cor. of rejected revision survey and marks on bearing trees.

The witness cor. of sec. 24, established by Mensch in 1910, which is marked by a cross on a basalt rock, witnessed as described by the surveyor general, bears S.47°W., 86 lks. dist. I now destroy this cor.; also marks on bearing trees.

George Grubb - For: U.S. Forest Service - Feb. 1981 - M 86-68

Found - 1" I.P. firmly set 4" above ground with a 1916 GLO brass cap, properly marked.

A 43" D.Fir snag, with no scribing visible on rotted blaze, bears N.63°W., 35.6 ft.

A protruding point of bluff with no orig. chisel marks visible, remarked "X BO", bears S.59°W., 3.7 ft. (Rec. S.51°W., 4.0 ft.) A 4"x4" X is at the exact bearing point.

New BT - 10" Hemlock bears N.13°W., 16.9 ft. scribed "X BT" on a double blaze with brass washer stamped "LS 397" nailed into lower blaze.