

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4163)

At point midway on W. bdy. of sec. 18 (4.73 chs. S.0°47'W. of the ¼ sec. cor. on E. bdy. sec. 13, T26S R2W) I establish ¼ sec. cor. on W. bdy. of sec. 18, as follows:
Set a basalt stone 15x10x8 ins., 10" in the ground for ¼ sec. cor. on W. bdy. of sec. 18, marked ¼ on E. face, from which
A Fir 30" dia., bears N.37°E., 31 lks. dist. mkd. ¼ S18 BT
A Cedar 10" dia., bears S.57°E., 52 lks. dist. mkd. ¼ S18 BT.

Fd. and tied corner in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4263)

Don E. Garrett - For: United States of America - Oct. 1972
M 47-7

Set brass cap marked "T26S R1W ¼ S18 1972 RPLS 544.", from which
14" Fir bears N.32°E., 58.4 ft. scribed ¼ S18 BT.
13" Fir bears S.21½°E., 60.2 ft. scribed ¼ S18 BT.

Fd. OK, Feb. 4, 1992 by DCSO - C.S. File 64/23-21

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011C

Fd. 3" brass disk stamped "RPLS 544 T26S R2W R1W ¼ S18 1972"
(10-16-07)
N. 606721.699
E. 4290330.605

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24042-3)

The ¼ sec. cor. of sec. 18 only, on the W. bdy. of T. 26 S., R. 1 W., reestablished by proportionate measurement by Garrett, in 1972. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with a brass cap (properly) mkd. from which the bearing trees mkd. by Garrett
A fir snag, 25" dia., bears N.31½°E., 58.5 ft., with a healed blaze. Continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 30" dia., bears S.23°E., 60.1 ft., with a healed blaze.
and a new bearing tree
A cedar, 6" dia., bears N.55¾°E., 24.1 ft., mkd. X BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center. Alum. angle iron driven alongside each monument.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/7/2022 - C.S. File 67/54-17

Found - 3" brass cap on 2" I.D. iron pipe, down 1"
Burned 23" Fir snag N.32°E., 58.4 ft. fully healed, double blaze.
Sawn burnt 26"x1' D.Fir stump S.21½°E., 59.7 (rec. 60.2) B&D to 3½" PK nail top center.
Unrecorded BT
Burnt-dead 7" cedar high-low X BT blaze N.55°E., 24.1 ft.
New - 43"x3 ft tall sawn, burned D.Fir stump N.27½°W., 33.6 ft. 3½" mag nail, top center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Mon on large flat bench 10 ft. north of Ⓞ gravel driveway running E&W.
See sketch in file
Lat: 43°18'23.96"N Long: 122°52'23.63"W