

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13 only, T26-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4066-67)

Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 12, 13 and 18 marked T26S S7 on NE.; R1W S18 on SE.; R2W S13 on SW.; and S12 on NW. faces, with 2 notches on N. and 4 notches on S. faces, from which
A Maple 5" dia., bears N.45°E., 31 lks. dist. mkd. T26S R1W S7 BT.
A Maple 4" dia., bears S.20°E., 49 lks. dist. mkd. T26S R1W S18 BT.
A Fir 48" dia., bears S.85°W., 41 lks. dist. mkd. T26S R2W S13 BT.
A Fir 24" dia., bears N.55°W., 55 lks. dist. mkd. T26S R2W S13 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4086)

No trace is found of the cor. or the NE. or SE. BTs. The other BTs are standing with marks yet legible. I re-establish the cor. in its original position as the cor. of secs. 12 and 13, T26S R2W only, as follows:
Set a basalt stone 12x10x8 ins., 8" in the ground for cor. of secs. 12 and 13, marked with 2 notches on N. and 4 notches on S. edge, from which
A Fir 48" dia., bears S.85°W., 41 lks. dist. mkd. T26S R2W S13 BT.
A Fir 24" dia., bears N.55°W., 55 lks. dist. mkd. T26S R2W S12 BT.

Fd. and tied in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4264)

Ben B. Irving, Wit: N.E. Richardson; Les Kershner; Geo. Riddle - Aug. 23, 1945 - C.S. File 38/40

Found Rock in mound of rock as described, except notches omitted, from which
24" Fir N.55°W. in place, old scribe marks visible.
48" Fir S.85°W., 41 lks., dead, figures burned off.
New BT:
8" Fir S.36°W., 21 lks. mkd. T26S R2W S13 CS BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100504

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13 only, T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Mar. 5, 1966 - C.S. File 52/77

Found - Mound of stones.
Orig. 48" Fir, S.85°W., 27.1 ft. (face) now burned
snag, no scribing found.
Orig. 24" now 30" Fir, N.55°W., 36.3 ft. (face
slope), alive & orig. bark scribe "12" &
rescribed "T26S S12 R2W CS BT".
8" now 11" Fir S.40°W., 13.9 ft. (slope) not
S.36°W., good scars, we do not open.

Set Brass cap in mound of stone & mkd:
County Surveyors Office 1966

	T 26 S	
R2W	$\frac{S}{S} \frac{12}{13}$	R1W

All BTs in good condition. Do not mark any new trees.

Fd. and used in BLM resurvey by Lynn M. Roseberry, Cadastral
Surveyor, under Group #644, Surveyed April 1968 - (DCSO
records Vol. 34 Page(s) 14268-69)

Fd. OK by K. Hoffine, Oct. 1999 - M133-59

Ken Hoffine - For: Lone Rock Timber Management Co. - July
2010 - M161-10

Found - 1966 Douglas County brass cap in mound of stones
27" D.Fir snag bears N.54½°W 34.8 ft (rec. N.55°W.,
34.65 ft) healed face and tag.
15" D.Fir bears S.45½°W., 12.5 ft (record S.46½°W.,
12.5 ft) healed face and tag.
Corner lies on steep south facing slope approx. 80 feet south
of bottom of rock bluff.