

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION CC for Secs. 6 & 7 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Pg 4166)

Set a basalt stone 16x12x12 ins., 11" in the ground for closing cor. of secs. 6 and 7, marked CC on E. with 1 groove on N. and 5 grooves on S. face, from which
A Chinquapin 10" dia., bears N.72°E., 44 lks. mkd. T26S R1W S6 BT.
A Madrone 6" dia. bears S.25°E., 28 lks mkd T26S R1W S7 BT

Fd. and tied in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4265)

Fd. OK in BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor, under Group #644, Surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14270)

Don E. Garrett - For: United States of America - October 1972
M 47-7

Set Brass cap mkd. "T26S S6 S7 R1W T26S R2W S12 1972 RPLS 544", from which
13" Fir bears N.6°E., 10.1 ft. scribed T26S R1W S6 BT.
11" Fir bears S.48½°E., 32.8 ft. scribed T26S R1W S7 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - April 19, 1987 - C.S. file 62/40-16 & 17

C.S. 62/40-17: From the 1910 Mensch retracement:
Found - An orig. 16x12x12 ins. basalt stone, now measuring 7"x12"x2" high on portion protruding from ground. Because of severe frost cracking, we do not remove to examine further.

From Garrett Survey M 47-7:
Found - On the E. edge of above stone is a 1/2" I.D. Iron pipe protruding 3" above ground.

(Bearings and distances measured from 1/2" Iron pipe)
From 1910 retracement, a Madrone 6" dia. now a 9" DBH Madrone, bears S.25°E., 18.9 ft. as per rec. No evidence found of scribing in previously opened blaze.

No evidence found of NE. Chinquapin BT.

We add new closing corner from Garrett Survey M 47-7, a 3" dia. brass cap on a 2" I.D. Iron pipe protruding 8" above ground, bears East, 12.04 ft. dist. (as per M47-7) We also tie SE. BT, for the above mentioned cap:

(Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Originally an 11" Fir scribed T26S R1W S7 BT, now a 13" DBH D.Fir with a fully healed double blaze, bears S.59°E., 42.5 ft.
A New BT, a 15" DBH D.Fir scribed CC T26S R1W S6 CS BT on a double blaze, bears N.55°E., 14.6 ft.
Monument is at East edge of old clear cut on a still definite N-S cutting line and is S. approx. 350 ft. from a creek, coursing N.75°E.
C.S. 62/40-16 AND
(Closing corner for Secs. 6 & 7 only, T26-1 from Garrett survey M 47-7)
Found - A 3" dia. Brass cap mkd. T26S R2W S12 S6 S7 1972 RPLS 544 on a 2" I.D. Iron pipe, firmly set and protruding 8" above ground.
13" Fir now a 15" DBH D.Fir with a fully healed double blaze, bears N.6°E., 10.1 ft.
An 11" Fir now a 13" DBH D.Fir with a fully healed double blaze, bears S.48½°E., 32.8 ft.
A USFS metal witness sign and post bears South 4.5 ft. previously unrecorded.
We add original 1910 closing corner as set by Mensch:
This closing corner is monemented by the original 16x12x12 basalt stone, now a broken 12x7 in. stone protruding 2" above ground with no marks visible. (We do not disturb)
Garrett's 1/2" I.P. on E. edge of stone protruding approx. 3" above ground. This iron pipe bears West, 12.04 ft. from brass cap monument. (agrees w/record M 47-7)
Monument is on East edge of old clear cut on a still definite N-S cutting line and is South approx. 350 ft. from a creek coursing N.75°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/4/2024 - C.S. File 67/59-15

Found - 3" brass cap (properly mkd) proj 12" above ground. Burned, dead 24"x24" double trunk D.Fir N.2°E., 8.6 ft. (rec. N.6°E., 10.1 ft) add 3½" mag nail, right side center.
Burned to ground D.Fir S.48½°E., 32.8 ft to remains. Post & metal witness sign south 4.5 ft.
The original closing corner monumented with 7"x12"2" stone & ½" IP bears west 12.04 ft From which:
Burned, dead 8" madrone S.25°E., 18.9 ft blaze gone. 24"x24" double trunk D.Fir N.55°E., 16.3 ft. (rec. 14.6 ft) add 3½" mag nail right side center.
continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - Burned, dead 29" D.Fir S.18°E., 26.6 ft. with 3" mag
nail right side center.

Note - Area burnt 9/2020
Compass decl. 14¼°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

N 180723.882 E 286336.671