

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4166-67)

-----  
At a point on the W. bdy. of sec. 6, 40.00 chs. North of the closing cor. of secs. 6 & 7 and 5/25 chs. S. of the ¼ sec. cor. on E. bdy. of sec. 1, T26S R2W., I establish ¼ sec. cor. of sec. 6 as follows:  
A Fir 30" dia., I mark ¼ S6 on E. side, from which  
    A Hemlock 10" dia., bears N.32°E., 31 lks. mkd. ¼ S6 BT.  
    A Hemlock 10" dia., bears S.31°E., 20 lks. mkd. ¼ S6 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24044-5)

-----  
The ¼ sec. cor. of sec. 6 only, on the W. bdy. of the T26S R1W, monumented with the remains of the original cor. tree, a fir stump, 33" dia., with a healed blaze on the east face, and axe marks on the north and south faces, from which the remains of an original bearing tree  
    A hemlock snag, 10" dia., bears S.31°E., 13.2 ft., with scribe marks 4 visible on partially healed blaze.  
    (Original)

At the corner point  
Saw the cor. tree stump flush with the surface of the ground and drive an iron rod, 30" long, 5/8" dia., 26" in the center of the stump, with aluminum cap mkd.

T26S  
R2W R1W  
    |  
    ¼  
    S6  
    |  
    2019

from which new reference monuments  
    An iron rod, 30" long, 5/8" dia., driven 27" in the ground, for a reference monument, bears N.48°01'55"E., 13.78 ft., with aluminum cap mkd. RM1 T26S R1W S6 13.78 FT TO COR 2019 and an arrow pointing to the cor.  
    An iron rod, 30" long, 5/8" dia., driven 30" in the ground, for a reference monument, bears S.50°17'06"E., 12.09 ft., with aluminum cap mkd. RM2 T26S R1W S6 12.09 FT TO COR 2019 and an arrow pointing to the cor.  
The sawed cor. tree stump is laying alongside the cor., with scribe marks S6 visible on opened healed blaze.