

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100646

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4068-69)

Set Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner marked ¼ S on W. face, from which
A Chinquapin 12" dia., bears N.51°E., 29 lks. dist. mkd. ¼ S BT.
A Hemlock 6" dia., bears N.80°W., 19 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4084)

(Page 4084)
The ¼ sec. cor. is not found after careful search. Set temp. ¼ sec. cor.
(Same Page)
Set a basalt stone 15x8x6 ins., 10" in the ground for ¼ sec. cor. on E. bdy. of sec. 1, T26S R2W mkd. ¼ on W. face, from which
A Chinquapin 12" dia., bears S.42°W., 23 lks. dist. mkd. ¼ S1 BT.
A Hemlock 12" dia., bears N.89°W., 9 lks. dist. mkd. ¼ S1 BT.

Fd. and tied in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4266)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam, crew - April 17, 1961 - C.S. File 52/77-4

Found - Stone mkd. "¼" on West face.
Shattered stump of Hemlock, N.89°W., 5.9 ft., scribe mark "S" plainly visible.
All trace of SW. BT gone.
Set Iron pipe with brass cap mkd. County Surveyors Office
T26S R2W ¼ S 1 |
1961
New BTs- 11" Hemlock, S.56½°E., 11.4 ft. mkd. E ¼ S1 CS BT.
8" Hemlock N.36°E., 7.5 ft. mkd. E ¼ S1 CS BT.
Land has been logged to West.

Corner found OK, June 1966, V.R.Tracy, DCSO

continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100646

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24045)

The ¼ sec. cor. of sec. 1 only, perpetuated by Godfrey, in 1961; from orig. evidence no longer in existence; monumented with an iron pipe, 1¼" dia., firmly set, projecting 12" above ground, in a collar of stone, with A brass cap (properly) mkd from which the remains of the bearing trees mkd. by Godfrey

A decayed living hemlock, 16" dia., bears N.35¾°E., 7.8 ft., with scribe marks E¼ S1 CS visible on partially healed blaze.

A hemlock snag, 13" dia., bears S.53¾°E., 11.5 ft., with scribe marks BT visible on partially healed blaze.

and new bearing trees

A fir, 13" dia., bears S.69¼°W., 33.2 ft., mkd. ¼ S1 BT.

A fir, 7" dia., bears N.52½°W., 15.5 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each monument unless a similar marker was already in place.