

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4069)

Set a Cedar post 4½ ft. long, 4" sq., 24" in the ground for corner to Tps. 25 and 26 S., R's 1 & 2 West, marked T25S S31 on NE.; R1W S6 on SE.; T26S S1 on SW.; and R2W S36 on NW. faces, with 6 notches on each edge, from which
A Fir 30" dia., bears N.85°E., 116 lks. dist. mkd. T25S R1W S31 BT.
A Pine 16" dia., bears S.55°E., 45 lks. dist. mkd. T26S R1W S6 BT.
A Pine 16" dia., bears S.60°W., 66 lks. dist. mkd. T26S R2W S1 BT.
A Fir 36" dia., bears N.68°W., 138 lks. dist. mkd. T25S R2W S36 BT.

Cor. tied in GL0 resurvey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4083)

GL0 survey by C.M. Collier, Deputy Surveyor, under Special Instructions dated May 12, 1913 - (DCSO records Vol. 10 Page(s) 4266)

Intersect the point for the cor. of Tps. 25 and 26 S., R2W., located by reference to the bearing trees as described by the surveyor general; all traces of the cor. have disappeared. I re-establish this cor. in its original position, as follows:
Set a basalt stone 14x10x6 ins., 9" in the ground, for cor. of Tps. 25 and 26 S., R2W., marked with 6 notches on the N. and W. edges, witnessed by the original bearing trees as follows:
A Fir 30" dia., bears N.85°E., 116 lks. dist. Marks obliterated.
A Pine 16" dia., bears S.55°E., 45 lks. dist. Marks obliterated.
A Pine 16" dia., bears S.60°W., 66 lks. dist. mkd. T26S R2W S1 BT.
A Fir 36" dia., bears N.68°W., 138 lks. dist. mkd. T25S R2W S36 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 9, 1966 - C.S. File 52/77-16

Found - Orig. 16" now 30" Pine, S.60°W., 43.6 ft. scribe visible, on prev. opened scar. (Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100669

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 of T26-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 16" now 30" Pine, S.55°E., 29.7 ft., shows old scar, recorded as marks obliterated.
Orig. 30" now 40" Fir, N.85°E., 76.6 ft., shows fragmentary bark scribe, recorded as being obliterated. NW. BT gone.
Do not find stone as called for.
Set Brass cap at cor. mkd: County Surveyors Office
T25S R2W S 36 | R1W
T26S S 1
1966
New BTs- 7" D.Fir N.56°W., 28.2 ft. mkd. T25S R2W S36 CS BT.
15" Hemlock S.50°W., 8.1 ft. mkd. T26S R2W S1 CS BT.
Corner lies on NE. slope in mound of stone 12" high.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22781-2

The cor. of Tps. 25 & 26 S., R. 2 W., monumented with an iron post, 2" dia., firmly set, projecting 4" above a mound of stone, 2 ft. base, 1 ft. high, with brass cap (properly) mkd. from which the remains of the orig. BTs reported by Collier
A fir, 47" dia., bears S.87¼°E., 76.6 ft., with no marks visible. (Record, N.85°E.)
A pine, 37" dia., bears S.44°E., 29.7 ft., with no marks visible. (Record, S.55°E.)
A pine snag, 35" dia., bears S.60°W., 43.6 ft., with a healed blaze.
and bearing trees mkd. by the Douglas County Surveyor's Office in 1966
A hemlock, 31" dia., bears S.51¾°W., 7.9 ft., with a healed blaze.
A fir, 11" dia., bears N.57¾°W., 27.2 ft., with a healed blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24046)

The cor. of T25 & 26S, R2W, reported by Skeesick in 2010-11, monumented with an iron post, 1¼" dia. (Record, 2" dia.), firmly set, projecting 16" above ground, in a mound of stone, 2 ft. base, 12". high, with a brass cap (properly) mkd. from which the remains of the BTs reported by Skeesick
A fir, 45" dia., bears S.87¼°E., 76.6 ft., no marks visible. (Original)
A pine snag, 37" dia., bears S.44°E., 29.7 ft., no marks visible. (Original)
Continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 100669

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 of T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 32" dia., bears S.51 $\frac{3}{4}$ °W., 7.9 ft., with a healed blaze.
A pine snag, 35" dia., bears S.60°W., 43.6 ft., with a healed blaze. (Original)
A fir, 12" dia., bears N.57 $\frac{3}{4}$ °W., 27.2 ft., with a healed blaze.