

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 138100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4787)

Set a basalt stone 20x18x5 ins., 15" in ground for ¼ sec. cor. marked ¼ on N. face, from which
A Cedar 40" dia., bears S.37°W., 34 lks. dist. mkd. ¼ S6 BT.
A Fir 10" dia., bears N.54°W., 38 lks. dist. mkd. ¼ S31 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4092 and 4102)

(Page 4092)
The ¼ sec. cor., which is a basalt stone 5x18x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.
(Page 4102)
The old ¼ sec. cor., which I re-establish as the ¼ sec. cor. on N. bdy. of sec. 6, T27S R1W only, as follows:
I obliterate marks on N. face of stone and mark ¼ S on S. face, from which
A Cedar 36" dia., bears S.6°E., 42 lks. dist. mkd. ¼ S6 BT
A Cedar 40" dia., bears S.37°W., 34 lks. dist. mkd. ¼ S6 BT.
I obliterate marks on former bearing tree referring to sec. 31.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 17, 1969 - C.S. File 54/94-93

Found - 20x18x5 Corner stone, in place & mkd. "¼" on S. side 40" now 50" Cedar S.37°W., 22.4 ft., shows scribing. No trace of SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T26S R1W ¼ _____
T27S S 6
1969
New BT - 6" Hemlock S.36°E., 13.1 ft. mkd. "¼ S6 CS BT"
The ¼ sec. 6 only lies 117.6 ft. S.82°W. from ¼ sec. 31 only, on steep N. slope.