

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4162)

Set a conglomerate stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A madrone, 6" dia., bears N.83°E., 35 lks., mkd: ¼ S7 BT.

A madrone, 6" dia., bears S.49°E., 28 lks., mkd: ¼ S18 BT.

Don Garrett - For: United States of America - 10/1972 - M47-7

Set - Brass cap mkd: T26S R1W ¼ S7 S18 1972 RPLS 544

16" Fir bears N.54¾°W., 11.9' scribed ¼ S7 BT

15" Fir bears S.46¼°E., 6.2' scribed ¼ S18 BT

Mark Smalley, LS 2354 - For: Roseburg Forest Products - Jan. 21, 1992 - C.S. File 63/138-3

Found - Brass cap mkd: "T26S R1W ¼ S7, S18, 1972 RPLS 544

High fir stump bears N.54¾°W., 11.9 ft. w/alum tag.

High fir stump bears S.46¼°E., 6.2 ft. w/alum tag.

New BT - 20" fir stump w/nail in the top bears S.88°W. 20.0 ft
Corner in recent clearcut, off the 4710-074 road.