

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4156)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A chinquapin, 10" dia. bears N.38°E. 37 lks. mkd: ¼ S20 BT
A fir, 40" dia., bears S.81°W., 15 lks., mkd: ¼ S19 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Darrel Myers - Aug. 14, 1979 - C.S. File 60/34-9

Found - Orig. corner stone, marked "X" on top and "¼" on the west face, is firmly set in the ground. Stone measures 12x8x6"
13" Chinquapin bears N.24°E., 23.8 ft (Rec. N.38°E., 24.42') Has a nearly healed and decayed blaze. Some scribing visible.
A 37" D.Fir bears N.75°W., 8.9 ft. (Rec. S.81°W., 9.9 ft) Has a single healed blaze & bark scribing "S19 BT CS TA ≡"
Set - Moving the corner stone aside, I set in its place a 1" I.Pipe with a 2½" brass cap attached marked County Surveyors Office T26S R1W ¼ S19 S20 1979. I bury corner stone alongside pipe.
No new accessories marked.
Corner is located approx. 300 ft. north of F.S. Rd. #2618.