

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4156-7)

Point for cor. of secs. 17, 18, 19, & 20 falls on a basalt rock in place, 10x12x8", above ground, on which I cut a cross (X) at exact cor. point, with 3 notches S & 5 notches E of cross, from which

A cedar, 16" dia., bears N.42°E., 50 lks., mkd: T26S R1W S17 BT.

A fir, 30" dia., bears S.82½°E., 100 lks., mkd: T26S R1W S20 BT.

A maple, 7" dia., bears S.82°W., 59 lks., mkd: T26S R1W S19 BT.

A maple, 4" dia. bears N.25°W. 7 lks. mkd: T26S R1W S18 BT

Fd. & used on GLO corrective survey by Fred Mensch, US Surveyor, under Group No. 16, surveyed June/Nov. 1916 - (DCSO records Vol. 10 Page(s) 4175)

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Karen Reed - Aug. 30, 1982 - C.S. File 62/1-16

Found - Orig. 30" fir now 35" with good scar. I open and find scribed "20"

Orig. stone not found.

I found no trace of other 3 BTs.

Set - Using record bearing & dist from found orig N.82½°W. 66.0 ft., I SET a 1"x30" I. pipe with brass cap attached 8" into the ground along with an 18" high mound of stone 2 ft. wide at the base. Cap is marked "Douglas Co Surveyor T26S S18 S17 S19 S20 R1W 1982".

New BTs- 26" fir scribed "BT CS T26S R1W S17" in double blaze reading from bottom to top from uphill side of tree., bears N.5°E., 27.9 ft.

8" fir scribed "T26S R1W S19 CS BT" in double blaze bears S.33°W., 58.1 ft.

10" maple scribed "T26S R1W S19 CS BT" in double blaze bears S.70°W., 32.3 ft.