

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4160)  
-----  
Set a basalt stone 15x8x8", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which  
    A fir, 48" dia., bears S.3 1/2°E., 44 lks., mkd: 1/4 S17 BT.  
    A fir, 28" dia., bears N.81°W., 60 lks., mkd: 1/4 S18 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 4/11/1972 - C.S. File 52/77-33  
-----  
Found - Orig. 48", now 50" Fir, alive, S.3 1/2°E. 29.0', open to axe blaze, no scribe visible, partially decayed.  
        Orig. 28", now 30" Fir sawed stump, N.81°W. 39.6', scribe visible on opened blaze.  
        No trace of Basalt Corner Stone Found.  
Set- Brass Cap at Cor. Mkd: County Surveyors T26S R1W Office, 1972 1/4 S 18|S 17  
New BTs- 9" D.Fir N.51°E. 24.2 ft. scribed "1/4 S17 CS BT"  
          6" D.Fir N.89°W. 9.2 ft. scribed "1/4 S18 CS BT"  
This corner lies approx. 100' above N. Ump. Hwy. on very steep, south slope.

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011F  
-----  
Fd. 2 1/2" brass cap stamped "COUNTY SURVEYORS OFFICE T26S R1W 1/4 S18 S17 1972" (9-25-07)  
N. 606599.110  
E. 4295409.211