

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4161)

Set a conglomerate stone 18x8x6", 12" in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edge, from which
 An Alder, 8" dia., bears N.21°E., 33 lks., mkd: T26S R1W S8 BT.
 An Alder, 7" dia., bears S.70°E., 13 lks., mkd: T26S R1W S17 BT.
 A fir, 40" dia. bears S.31°W. 14 lks. mkd: T26S R1W S18 BT
 An Alder, 7" dia., bears N.53°W., 22 lks., mkd: T26S R1W S7 BT.

Douglas Co. Surveyors Office - Milo Godfrey - 3/1963 - C.S. File 52/77-11

Not found.
Fd. yellow tag only indicating cor.
On N edge old N.Umpqua Rd. just East of burnt Ck.
No BTs or cor rock fd.

Don Garrett - For: United States of America - 10/1972 - M47-7

Set - Brass cap, 6" below road surface, mkd: T26S R1W S7, S8, S17, S18, RPLS 544
 15" Fir bears S.66°W., 52.5' scribed T26S R1W S18 BT
 9" Fir bears N.32°W., 36.7' scribed T26S R1W S7 BT
 18" Fir bears N.27°E., 21.0' scribed T26S R1W S8 BT
 8" Fir bears S.55½°E., 78.4' scribed T26S R1W S17 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Tony Flores - March 15, 1979 - C.S. File 60/24-20

Found - A 2½" Brass cap buried 5" under the road surface, stamped T26S R1W S7 S8 S18 S17 1972 RPLS 544-1972 Possible orig. BT, a 42" D.Fir bears N.39°W., 44.4 ft. Has a single healed blaze. I open this tree but find no scribing. No sign of orig. corner stone. I discount this tree as being an orig. Mensch BT.
 A 13" W.Fir bears N.31°30'W., 36.7 ft. Some scribing visible on a nearly healed double blaze.
 A 20" D.Fir bears N.29°30'E., 20.3 ft. has healed double blazes.
 A 12" D.Fir bears S.55°E., 78.4 ft. has double healed blazes.

continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - A 17" D.Fir bears S.66°W. 52.5 ft to base of tree at center (tree is leaning) has double healed blazes
A 2½" Brass cap on a 1"x36" I.P. as a witness corner. This W.C. monument bears North, 50.0 ft. from the true corner monument and is marked County Surveyor's Office T26S R1W W C S7 S8 S18 S17 South 50.0 1979.

New - (these BTs are referenced to the witness cor. monument)
A 20" W.Fir bears N.73°30'E., 61.9 ft. scribed "T26S R1W S8 WC CS BT" on a double blazes.
A 21" D.Fir bears N.35°W., 30.8 ft. scribed "T26S R1W S7 WC CS BT" on double blazes.
Corner lies in left edge of P.S. Road #2604

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011F

Fd. 2½" brass cap stamped "COUNTY SURVEYORS OFFICE T26S R1W S7 S8 S18 S17 WC SOUTH 50.0 1979" (10-16-07)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/5/2024 - C.S. File 67/59-12

Found - Brass cap buried ±2 ft. below road surface, 7 ft. south of road centerline.
Burnt-dead 22" D.Fir S.55°E., 78.4 ft. healed double blaze.
Burnt 32"x3 ft. fir stump S.66°W. 53.2 ft. (rec. 52.5 ft) healed lower blaze.
2½" brass cap W.C. bears North 50.0 ft. at top of cut bank.
BTs to witness corner.
Sawn, burnt, 34"x2 ft. W.Fir stump N.73°30'E., 61.9 ft. evidence of blaze inside, add 3½" mag nail top center.
Sawn, burnt, 32"x2 ft. D.Fir stump N.35°W., 30.8 ft., evidence of blaze inside, add 3½" mag nail top center.

New ref. measured from true corner -
A 5/8"x30" Iron rod with DCS0 plastic cap S.56°E., 26.0 ft., proj 1".

Note - True corner is in S. Edge of F.S. Rd #2604.
Area burnt 9/2020
Compass decl. 14¼°E.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 175502.538 E 291567.279