

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200560

PRIMARY CORNER DESCRIPTION N 1/16 Secs 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Don Garrett - For: Henry Bridgeman - 11/1964 - C.S. 51/290-2

Set - 5/8"x 30" iron rod.
18" Cedar N.53°W., 35.2' scribed N 1/16 S7 BT.
54" Fir stump N.53°W., 14.5' scribed N 1/16 S8 BT.

George Grubb - For: USFS - April 1981 - M87-37

Found - 5/8" iron rod projecting 12" above the ground.
Set - 2"x30" iron pipe, 24" in the ground, in a 2½" dia.,
mound of stone with a 3" brass cap mkd:
T26S R1W
N 1/16
S7|S8
1981
PLS 397
from which BTs marked by Garrett in 1964
A 52" D.Fir stump with bark scribing "N 1/16 S8 BT"
visible bears N.52°E., 16.8 ft. (rec. N.53°W.,
14.5 ft.)
A 21" Cedar with scribe marks visible on partially
healed blaze bears N.50°W., 35.8 ft. (rec.
N.53°W., 35.2 ft.)
New BT - A 7" D.Fir bears N.56°E., 39.8 ft. scribed "N 1/16
S8 BT"

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 6/14/2023 - C.S. File 67/56-34

Found - 3" brass cap (properly mkd) on 2" iron pipe up 2" in
rough stone mound
Very burned, rotted 36"x4' stump N.52°E., 16.8 ft.
Burnt, sawn 36"x2½ ft. cedar stump, S.50°W., 35.3 ft
full healed single blaze, add 3½" mag nail top
center.
Burned, dead 15" D.Fir N.56°E., 39.2 ft. (rec. 39.8
ft) fully healed single blaze, add 3½" mag nail
right side center.
Note - Corner in bottom of shallow draw large burned reprod
NE quad. Rest clear cut.
Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
179413.608 N 291517.639 E

continued next page

1

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200560

PRIMARY CORNER DESCRIPTION N 1/16 Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jack White, S&F Land Services - For: USDA Forest Service
Region 6 - 1/2025 - M185-80 A&B

Found - Held an iron pipe, 2" dia., with a 2½" brass cap,
from which

Dead, fire damaged BTs:

54" D.Fir bears N.54°57'40"E, 16.8' (Rec. 1964 &
2023: N.53°W., 14.5' and N.52°E., 16.8')

34" Cedar stump bears N.51°06'06"W., 35.5' (Rec 1964
& 1981: N.53°W, 35.2', N.50°W., 35.8').

14" D.Fir, mkd. with a healed blaze, bears
N.58°50'31"E., 39.40' (Rec 1981- N.56°E., 39.8').

Set two reference monuments - Rebar, 5/8" dia., 30" long,
with a yellow plastic cap mkd: S&F Land Services: Bearing
N.88°07'08"E., 26.38' and N.01°28'26"W., 10.22'.