

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCS0 records Vol. 10 Page(s) 4164)

Set basalt stone 18x10x8", 12" in the ground for cor of secs 5, 6, 7, & 8 mkd with 5 notches on S & E edges, from which

A fir, 6" dia., bears N.33°E., 87 lks. mkd: T26S R1W S5 BT

A fir, 40" dia. bears S.53°E. 126 lks. mkd: T26S R1W S8 BT

A fir, 18" dia. bears S.4½°W. 108 lks. mkd: T26S R1W S7 BT

A chinquapin, 8" dia., bears N.59°W., 41 lks., mkd: T26S R1W S6 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1970 - C.S. File 52/77-29

Found - Corner stone, in place with "X" on top & 5 notches on S & E.

Orig. 6" now 14" fir alive, N.33°E., 57.4 ft. open & find "\5" scribe.

Orig. 18" now 40" fir alive S.4½°W., 71.3 ft. shows good scar, we tag.

Orig. 40" now 60" fir alive, S.53°E., 83.2 ft. shows good scar, we tag.

Set - Possible remains of NW orig. BT down & badly decayed
 Brass cap at cor. mkd: COUNTY SURVEYORS T26S R1W
 (Reset old stone OFFICE S 6 | S 5
 alongside) 1970 S 7 | S 8

New BTs- 18" D.Fir N.49°W., 14.2 ft. mkd: T26S R1W S6 CS BT
 12" D.Fir N.17°E., 13.7 ft. mkd: T26S R1W S5 CS BT
 14" D.Fir S.67°E., 6.6 ft. mkd: T26S R1W S8 CS BT
 6" D.Fir S.20°W., 18.7 ft. mkd: S7 CS BT.

This corner lies on very gentle almost flat, easterly slope, about 1400 ft. east of Burnt Creek access road. #2644

Douglas Co. Surveyors Office - Randall Smith - Stephen Flause - Jan. 15, 1986 - C.S. File 62/31-9

Found - 1970 County brass cap protruding 12" above ground.

A 15x8x7" stone with 5 marks found on one edge. (Rec. 18x8x7" stone with 5 marks on south & east edges orig. and an "X" on top (fd per 1970 Ren.) lays along northeast edge of IP.

Orig BT, a 6" now 10" dia. 3½ ft. high rotted D.Fir stump scribing found in previously opened blaze " / 5" bears N.33°E., 57.7 ft. (Rec. N.33°E., 37.4 ft. to face of blaze.)

Orig. BT, a 40" now 67" dia. D.Fir with a fully healed single blaze bears S.53°E., 83.2 ft. (agrees with record). continued next page

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. BT, a 18" now 46" dia. D.Fir with a fully healed single blaze bears S.6°W., 71.3 ft. (Rec. S.4½°W., 71.3 ft.)
No evidence of NW BT found.
18" now 17" dia. 40 ft. high D.Fir snag with a partially healed single blaze scribing visible "T26S R1W S6 CS BT" bears N.49°W., 14.2 ft.
12" now 13" dia. D.Fir with a fully healed single blaze bears N.17°E., 13.7
14" now 17" dia. D.Fir with a fully healed single blaze bears S.67°E., 6.6 ft.
6" now 6" dia. dead D.Fir with a fully healed single blaze bears S.20°W., 18.7 ft.
New BT - 10" dia. D.Fir double blazed and scribed "T26S R1W S6 CS BT" bears N.9°W., 49.0 ft.
Corner lies on level ground.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/14/2023 - C.S. File 67/56-35

Found - 2½" DCS0 brass cap (properly mkd) on 1" ID IP up 12", orig. stone on east edge.
Burned-dead 72" D.Fir S.53°E., 83.2 ft. fully healed single blaze, add 3½" mag nail right side center.
Burned-dead 55" D.Fir S.6°W., 71.3 ft. fully healed single blaze add 3½" mag nail right side center.
Root hole N.49°W., 14.2 ft. rec. D.Fir.
Burned dead 17" D.Fir N.17°E., 13.7 ft. fully healed single blaze, add 3½" mag nail right side center.
Burned, dead 22" D.Fir S.67°E., 6.3 ft. (rec. 6.6 ft.) healed single blaze add 3½" mag nail right side center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Corner is on level ground in burned very old thinning approx. 170' west from end of dirt road.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
180724.599 N 291534.444 E