

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 238100

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for sec. 5 only, T27-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4787-88)

-----  
Set a basalt stone 12x8x8 ins., 8" in ground for 1/4 sec. cor. marked 1/4 on N. face, from which

A Hemlock 30" dia., bears N.31°E., 19 lks. dist. mkd. 1/4 S32 BT.

A Hemlock 12" dia., bears S.38°E., 15 lks. dist. mkd. 1/4 S5 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4093 and 4101)

-----  
(Page 4093)

The 1/4 sec.cor. which is a basalt stone 4x8x8 ins., above ground, firmly set, mkd. and witnessed as described by the surveyor general.

(Page 4101)

The old 1/4 sec. cor. which I re-establish as the 1/4 sec. cor. on N. bdy. of sec. 5, T27S R1W only, as follows:

I obliterate marks on N. face of stone and mark 1/4 S on S. face, from which

A Hemlock 12" dia., bears S.38°E., 15 lks. dist. mkd. 1/4 S5 BT.

A Fir 6" dia., bears S.35°W., 25 lks. dist. mkd. 1/4 S5 BT. I obliterate marks on former bearing trees referring to S.32.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 4, 1969 - C.S. File 54/94-74

-----  
Found - 12x8x8 stone, firmly set, mkd. "1/4".  
12" now 15" Hemlock S.38°E., 9.9 ft., scribe visible.

6" Fir, now 8" Hemlock S.35°W., 16.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T26S  
T27S R1W 1/4       
                  S 5  
                  1969

Bearing trees OK and tagged.