TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4161-2)

Set a conglomerate stone 18x9x5", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 10" dia., bears N.50°E., 22 lks., mkd: ¼ S8 BT.
A fir, 10" dia., bears S.65°W., 29 lks., mkd: ¼ S17 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1970 - C.S. File 52/77-32

Found - Old Corner Stone, in place, mkd: "+" on top & "¼" on SW Side.
Orig. 10",now 18" Fir, alive, N.50°E. 14.5 ft., shows scar. We Rescribe: "¼ S 8 CS BT".
Orig. 10", now 15" Fir, alive, S.65°W., 19.1 ft., we open & find scribe revrd we Rescribe "¼ S17 CSBT"

Set - Brass Cap at Cor. mkd: County Surveyors Office 1970

T26S R1W
S 8
S 17

New BT - 12" Cedar S.64°W. 39.0 ft. mkd: "¼ S17 CS BT.
This corner lies in vine maple thicket, down logs & old logging debris.
N, Umpqua Highway bears South approx. 450 ft., put tag at Hwy. on North Side, approx. 200 ft. west of 32 mile post.