

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 240540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

George Grubb - For: US Forest Service - April 1981 - M87-37

Set - 2"x30" iron pipe 24" in the ground with a 3" brass cap
mkd: T26S R1W C¼ S8 1981 PLS 397
9" Hemlock bears S.73°E., 22.2 ft. scribed "C ¼ S8 BT"
7" hemlock bears S.17°W., 20.5 ft. scribed "C ¼ S8 BT"

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/9/2022 - C.S. File 67/55-7

Found - 3" brass cap (properly mkd) on 2" ID iron pipe up 8"
Burned, dead 15" hemlock S.75°E., 22.0 ft. (rec. S.73°E., 22.2 ft.) fully healed double blaze, add 3½" mag nail right side center.
Burned, dead 14" hemlock S.14°W., 20.6 ft. (rec. S.17°W., 20.5 ft.) fully healed double blaze, add 3½" mag nail right side center.
New - Burned, dead 40" D.Fir N.47°E., 18.6 ft. 3½" mag nail right side center not blazed or scribed.
Burned, dead 54" D.Fir S.25°E., 29.0 ft. 3½" mag nail right side center not blazed or scribed.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Lat: 43°19'15.49" N Long: 122°50'40.01" W

Jack White, S&F Land Services - For: USDA Forest Service Region 6 - 1/2025 - M185-80 A&B

Found - Held an iron pipe, 2" dia., with a 3" brass cap, from which
Dead, fire damaged BTs:
15" Hemlock bears S.71°20'34"E., 22.09' (rec. S.73°E., 22.2').
7" Hemlock bears S.17°30'52"W., 20.53' (S.17°W., 20.5').
44" D.Fir bears N.49°54'44"E., 18.49' (N.47°E., 18.6').
60" D.Fir bears S.25°45'29"E., 28.81' (S.25°E., 29.0').
Set two reference monuments - Rebar, 5/8" dia., 30" long, with a yellow plastic cap mkd: S&F Land Services: Bearing S.60°14'16"E., 21.43' and S.54°13'44"W., 20.17'.