

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4165)

A fir, 5" dia., for 1/4 sec. cor. I mark 1/4 S5 on N & 8 on S side, from which

A fir, 12" dia., bears N.30°W., 21 lks., mkd: 1/4 S5 BT.

A fir, 7" dia., bears S.46°W., 25 lks., mkd: 1/4 S8 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1970 - C.S. File 52/77-27

Found - Corner Tree gone.
Orig. 12", now 13" Fir, now 15' high snag, N.30°W. 13.9 ft., scribe visible on unhealed blaze.

Set - Brass Cap at Cor. mkd: County Surveyors T26S R1W
Office 1/4 S 5
1970 S 8

New BTs- 14" D.Fir N.30°E. 24.8 ft. mkd: "1/4 S5 CS BT".

7" D.Fir S.63°W. 33.0 ft. mkd "1/4 S8 CS BT"

This cor. lies on steep, easterly slope about 300 ft. west of Fall Creek, good blazed line East of corner.