

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4100)

Point for cor. of secs. 32 and 33 falls on a basalt rock in place, 6x12x12 ins. above ground on which I cut a cross (X) at exact cor. point, with 4 notches on E. and 2 notches on W. of cross, from which

A Fir 8" dia., bears N.80°E., 14 lks. dist. mkd. T26S R1W S33 BT.

A Fir 10" dia., bears N.65°W., 26 lks. dist. mkd. T26S R1W S32 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 5, 1969 - C.S. File 54/94-30

Found - No trace of corner stone.
8" now 13" Fir, N.72°E., (Rec. N.80°E.) 9.2 ft. I find this tree to be a Cedar, scribe visible.
10" now 15" Fir N.65°W., 17.2 ft., opened for scribe "S3".

Set Brass cap at cor. mkd: County Surveyors Office
T 26 S R1W S 32 | S 33
T 27 S 1969 S 4

Bearing trees OK and tagged.