

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4137)

Set a basalt stone 15x12x8", 10" in the ground for cor. of secs. 28, 29, 32, & 33 mkd with 1 notch on S & 4 notches on E edge, from which
A fir, 36" dia. bears N.36°E. 24 lks. mkd: T26S R1W S28 BT
A fir, 24" dia. bears S.64°E. 20 lks. mkd: T26S R1W S33 BT
A fir, 40" dia. bears S.68°W. 30 lks. mkd: T26S R1W S32 BT
A fir, 36" dia. bears N.34°W. 19 lks. mkd: T26S R1W S29 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Darrel Myers - Aug. 14, 1979 - C.S. File 60/34-11

Found - Original corner stone set firmly in place, measures 14x10x8" no marks visible on stone.
A 36" D.Fir snag bears N.37°E., 15.84 ft. and has a single healed blaze.
A 25" Fir stump (hi stump) bears S.59°E., 13.8 ft. (Rec. S.64°E., 13.2 ft) has a single healed blaze
A 36" D.Fir stump bears S.70°W., 19.8 ft. has a single healed blaze. (Rec. S.68°W.)
36" windfall is now a stump. Root hole bears N.34°W., 12.5 ft. No marks or scars visible.

Set - Moving corner stone aside, I set in its place a 2½" brass cap on a 1" galv. I.P. Cap marked "County Surveyors Office T26S R1W S29 S28 S32 S33 1979". I bury corner stone alongside pipe.

New - Set a 5/8" iron rod with a 1½" alum, cap in orig. SW BT stump and marked cap "RM". Cap bears S.67°30'W., 18.85 ft.
A 5/8" I.Rod with a 1½" Alum, cap marked "RM" bears N.33°E., 13.02 ft.

This corner is 100 ft. south of F.S. Rd. #2627 in a proposed clearcut. Any new BTs set will be cut.