

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4138)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor., mkd ¼ on W face, from which

A fir, 24" dia., bears N.50°E., 21 lks., mkd: ¼ S28 BT.

A fir, 24" dia., bears S.67°W., 20 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - Gary L Langlitz - Clell E Goodwin - A Vic Cangie - M. Lenora Ladig - 10/13/1975 - C.S. 57/36-16

Found - Both original bearing trees which are now stumps. We open both stumps and find good scribing on both. The positions of the orig BTs is such that the record distances will not intersect. We find the point established at record bearing and distance from the NE stump also causes the bearing to the SW stump to agree with the record bearing.

At the corner point as determined per the above explanation, we set a 5/8"x30" Iron Rod with aluminum cap attached, marked,
DOUGLAS CO SURVEYOR

¼
29|28
1975

BTs - An orig. 24" D.Fir now a 28" stump bearing N.50°E., 13.9 ft. (Record N.50°E., 13.9 ft.)
An orig. 24" D.Fir, now a 28" stump bearing S.67°W., 19.4 ft., (Record S.67°W., 13.2 ft).

We mark the following new BTs

A 16" Hemlock bears S 14°E., 101.3 ft. scribed "¼ S28 CS BT" on a double blaze.

A 7" Hemlock bears N.69½°W., 83.9 ft. scribed "¼ S 29 CS BT" on a double blaze.

Compass declination setting 20°E.

Note - This renewal was originally typed in T26S R1E but was added to the correct T&R 4/19/2012 - JC DCSO