TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4143)

Set a basalt stone 18x10x6", 12" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & E edges, from which

A chinquapin, 9" dia., bears N.31°E., 33 lks., mkd: T26S R1W S9 BT.
A chinquapin, 9" dia., bears S.85°E., 34 lks., mkd: T26S R1W S16 BT.
A madrone, 8" dia., bears S.20°W., 33 lks., mkd: T26S R1W S17 BT.
A sugar pine, 10" dia., bears N.30°W., 35 lks., mkd: T26S R1W S8 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - V. Tracy & Mike Stone - March 29, 1963 - C.S. File 52/77-10

Found - Rock at Cor, with 4 notches on S & E edges as called for in Gov't. notes. - Wooden Stake in mound of rock about 1' W. of Cor.
Dead Chinq. Snag N.31°E. 21.8 ft., scribing vis. on old face.
14" Chinq. S.85°E. 22.4 ft., shows good scars. Did not open.
A Stump Hole to NW & a rotten piece of Madrone Wood to SW approx. fit bearings & distances for NW & SW BTs.

Set - Brass Cap alongside Rock Mkd: County Surveyors Office
Pile Rocks around corner. 1963 T26S R1W S 8 | S 9 / S 17 | S 16

New BTs- 14" D.Fir S.7°W. 17.1 ft. Mkd: T26S R1W S17 CS BT.
20" Sugar Pine N.62°W. 22.9 ft Mkd T26S R1W S8 CS BT
18" D.Fir N.36°E. 63.7 ft. Mkd: T26S R1W S9 CS BT.
12" D.Fir S.28°E. 63.7 ft. Mkd: T26S R1W S16 CS BT.

Corner lies approx. 260 ft. North of N. Umpqua Highway and 130 ft East of Fall Creek.

FD Ok by VRT, DCSO 3/3/1970 - C.S. 52/77-23

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011I

Fd. 2½" brass cap stamped "COUNTY SURVEYORS OFFICE T26S R1W S8 S9 S17 S16 1963" (9-27-07)
N. 608990.929
E. 4300710.546