

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 338100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only, T27-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4788-89)

-----  
To edge of cliff upon which point for 1/4 sec. cor. falls. Set a basalt stone 15x10x5 ins., 10" in the ground for W.C. for 1/4 sec. cor. marked WC 1/4 on N. face, from which  
A Hemlock 24" dia., bears S.26°W., 7 lks. dist. mkd. WC 1/4 S4 BT.  
A Hemlock 20" dia., bears N.73°W., 47 lks. dist. mkd. WC 1/4 S33 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4093 and 4100)

-----  
(Page 4093)  
The witness cor. to the 1/4 sec. cor., which is a basalt stone 5x10x5 ins., above ground, firmly set, marked and witnessed as described by the surveyor general. (The true point for 1/4 sec. cor. is .20 chs. East)  
(Page 4100)  
The old witness cor. to the 1/4 sec. cor., which I re-establish as the witness cor. to the 1/4 sec. cor. on N. bdy. of sec. 4, T27S R1W only, as follows:  
I obliterate marks on N. face of stone and mark WC 1/4 on S. face, from which  
A Fir 14" dia., bears S.30°E., 21 lks. dist. mkd. WC 1/4 S4 BT.  
A Hemlock 24" dia., bears S.26°W., 7 lks. dist. mkd. WC 1/4 S4 BT.  
I obliterate marks on former bearing tree referring to sec. 33.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 1, 1969 - C.S. File 54/94-64

-----  
Found - Stone, firmly set, at Wit. Corner mkd. "WC 1/4".  
14" now 37" D.Fir S.30°E., 15.4 ft. (Rec. 13.4 ft.), shows good scar.  
24" now 31" Hemlock S.26°W., 4.6 ft. shows good scar.

This corner is a witness corner, 13.2 ft. West of true corner. True corner falls on bluff.

Set Brass cap at cor. mkd: County Surveyors Office  
T26S R1W W.C. 13.2' East  
T27S to 1/4  
1969 S 4

(Cont. Next Page)

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 338100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only, T27-1

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Bearing trees OK and tagged.  
Corner lies 4.0 ft. South of 40 ft. bluff.