

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4100)

Set a basalt stone 18x12x10 ins., 12" in the ground for 1/4 sec. cor. on S. bdy. of sec. 33, marked 1/4 on N. face, from which

- A Fir 10" dia., bears N.60°E., 25 lks. dist. mkd. 1/4 S33 BT.
- A Fir 24" dia., bears N.21°W., 12 lks. dist. mkd. 1/4 S33 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 1, 1969 - C.S. File 54/94-65

Found - No trace of Corner stone.
10" now 13" D.Fir N.60°E., 16.5 ft., opened for scribe.
24" now 27" D.Fir N.29°W., (Rec. N.21°W.) 7.9 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 26 S R 1 W
1/4 S 33
T 27 S
1969

Bearing trees OK and tagged.