

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4139-40)

Set a basalt stone 15x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A fir, 8" dia., bears N.15°W., 25 lks., mkd: 1/4 S21 BT.
 A fir, 5" dia., bears S.86°E., 4 lks., mkd: 1/4 S28 BT.

Douglas Co. Surveyors Office - John Powell - J. Heritage - May 21, 1973 - C.S. File 56/25-28

Found - 5" Fir, down & rotten S.86°E., 2.6 ft scribe visible S28.
 5x8x6 stone mkd. 1/4 on north face, firmly in ground.
 No trace of NW BT.
Set - Brass Cap at Cor. mkd. County Surveyors Office 1973 T26S R1W 1/4 S 21 / S 28
New BTs- 20" D.Fir, N.70°E., 9.2 ft. Scribed 1/4 S21 CS BT.
 18" D.Fir, S.5°E., 25.4 ft. scribed 1/4 S28 CS BT.