

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4144)

Set a granite stone 12x8x6", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A hemlock, 7" dia., bears N.11°E., 20 lks., mkd: 1/4 S9 BT.
 A cedar, 10" dia., bears S.40°W., 35 lks., mkd: 1/4 S16 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - March 1970 - C.S. File 52/77-23

Reported as not found.
After running line westerly & following old blazes - we find no trace of OBTs - area where cor. would be has been burned many years ago - only very young trees - extremely steep ground.

Maurice "Ed" Farr - For: Umpqua National Forest - Jan. 1977 - M63-20 - C.S. 58/138

Set - 1"x36" IP with a 2 1/2" brass cap stamped T26S R1W 1/4 S9 S16 PE 5188 1977. From which
 A 8" Hemlock, N.71°30'E., 19.8 ft. blazed & scribed "1/4 S9 BT"
 A 50" D.Fir, S.22°E., 18.4 ft. blazed & scribed "1/4 S16 BT".