

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4146)

Set a conglomerate stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A maple, 10" dia., bears N.14°E., 47 lks., mkd: ¼ S4 BT.
A maple, 7" dia., bears S.74°W., 14 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - March 1970 - C.S. File 52/77-25

Reported as not found.
No trace of OBTS fd. Cor. would fall in old logged unit & on very steep slope - burned.

Maurice "Ed" Farr - For: Umpqua National Forest - Jan. 1977 - M63-20 - C.S. 58/138

Set - 1" Iron rod, 6 ft. in the ground, with 1"x36" IP over the rod, a 2½" brass cap stamped T26S R1W ¼ S4 S9 PE 5188 1977. From which
7" D Fir, N 9°15'E , 99.0 ft blazed and scribed "¼ S4 BT"
10" D.Fir, S.7°15'E., 125.2 ft. blazed & scribed "¼ S9 BT"