

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 357700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 and 33 only, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3503-04)

A Fir 9" dia. for cor. of secs. 4, 5, 32 and 33, I mark T25S S33 on NE.; R1W S4 on SE.; T26S S5 on SW.; and S32 on NW. faces, with 4 notches on E. and 2 notches on W. sides, from which

- A Fir 6" dia., bears N.61°E., 9 lks. dist. mkd. T25S R1W S33 BT.
- A Fir 12" dia., bears S.24°E., 31 lks. dist. mkd. T26S R1W S4 BT.
- A Fir 7" dia., bears S.30°W., 26 lks. dist. mkd. T26S R1W S5 BT.
- A Fir 10" dia., bears N.28°W., 11 lks. dist. mkd. T25S R1W S32 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3574) (and duplicate pg. 4080A, Vol. 10)

The cor. of secs. 4, 5, 32 and 33, which is a Fir, 9" dia. mkd. and witnessed as described by the surveyor general. I re-establish this cor. as the cor. of secs. 32 and 33, T25S R1W only, by obliterating marks on bearing trees referring to T26S.