

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GL0 survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4126)</p> <p>-----</p> <p>Set a basalt stone 12x12x10", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which</p> <p>    A fir, 12" dia., bears N.65°E., 17 lks., mkd: ¼ S34 BT.</p> <p>    A fir, 28" dia., bears N.21°W., 46 lks., mkd: ¼ S33 BT.</p>
<p>Douglas Co. Surveyors Office - John Powell - W. Penley - J. Heritage - J. Byron - Aug. 13, 1971 - C.S. File 54/94-107</p> <p>-----</p> <p>Found - 10" D.Fir, now snag, N.65°E., 11.2 ft scribe visible ¼ S34 BT.</p> <p>        30" W.Fir, now snag, N.21°W., 30.4 ft scribe visible ¼ S33 BT.</p> <p>        Also stone at ¼ Cor. mkd. ¼ &amp; + on top.</p> <p>Set - 5/8" I. Rod along side stone. (As this area is to be thinned, Brass Cap would probably be lost through logging.)</p> <p>New BTs- 33" D.Fir, S.81°E., 12.0 ft. Scribed ¼ S34 CS BT.</p> <p>        16" D.Fir, N.56°W., 29.7 ft. Scribed ¼ S33 CS BT.</p>