

TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4130)

Set a basalt stone 24x12x12", 18" in the ground for cor. of secs. 15, 16, 21, & 22 mkd with 3 notches on S & on E edges, from which

- A fir, 8" dia. bears N.12°E., 32 lks. mkd: T26S R1W S15 BT
- A fir, 24" dia. bears S.86°E., 9 lks. mkd: T26S R1W S22 BT
- A fir, 6" dia. bears S.68°W., 16 lks. mkd: T26S R1W S21 BT
- A fir, 16" dia. bears N.57°W. 17 lks. mkd: T26S R1W S16 BT

Dennis Gaylord, USFS - Douglas Co. Surveyors Office -
Witness: James Davis - Aug. 32, 1978 - C.S. File 60/11-36

Found - Orig. Corner stone marked "X" on top & with 3 notches on the South & 3 notches on the east edge, is set firmly in the ground. Stone measures 10x11x18".

- A 44" D.Fir bears S.86°E., 5.94 ft. has a healed blaze.
- A 19" D.Fir bears N.12°E., 20.7 ft. (Rec. 21.12 ft.) has a healed blaze.
- A 30" D.Fir bears N.57°W., 11.22 ft. has a healed scar.
- A well decayed stump bears S.68°W., 10.56 ft. No marks or blazes visible.

Set - Referencing the corner stone, I set it aside and in its place I set a 1½" I.P. with a 2½" brass cap attached mkd. "County Surveyors Office T26S R1W S16 S15 S21 S22 1978".

I bury corner stone alongside iron pipe.

New BTs- A 25" Cedar, bears S.14°W., 41.7 ft. scribed "T26S R1W S21 CS BT" on a double blaze.

I placed County BT signs on all 4 trees.