TOWNSHIP 26 RANGE 01 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. SEcs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Fred Mensch, Deputy Surveyor - contract #797 dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4131-2)

---

Set a basalt stone 15x2x8", 10" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notches on E edge, from which

A maple, 5" dia., bears N.24°E., 50 lks., mkd: T26S R1W S10 BT.
A fir, 40" dia. bears S.19°E. 37 lks. mkd: T26S R1W S15 BT
A chinquapin, 5" dia., bears S.39°W., 45 lks., mkd: T26S R1W S16 BT.
A fir, 60" dia. bears N.53°W., 40 lks. mkd: T26S R1W S9 BT

---

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1970 - C.S. File 52/77-22

---

Found - Orig. 60", now 60" Fir Snag, N.53°W. 26.4 ft., scribe marks visible on decaying blaze.
Orig. 40", now 40" Fir Snag, S.l9°E., 42.0 ft., (Rec. 24.4').
No trace of Corner Stone or other Orig. BTs.
Ridge Call of 16.5 ft. West fits this point good.

Set - Brass Cap at Cor. mkd: County Surveyors T 26 S R 1 W
(Cap in Rock Mound) Office 1970

| S 9 | S 10 |
|---|---|
| S 16 | S 15 |

New BTs- 8" D.Fir N.37°W. 6.6 ft. mkd: T26S R1W S9 CS BT.
7" D.Fir S.58°W. 17.5 ft. mkd: T265 R1W S16 CS BT.
5" D.Fir S.76°E. 15.0 ft. mkd: S15 CS BT.
6" D.Fir N.31°E. 17.8 ft. mkd: S10 CS BT.

---

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011L

---

Fd. 2½" brass cap stamped "COUNTY SURVEYORS OFFICE T26S R1W S9 S10 S16 S15 1970" (10-23-07)
N. 608833.222
E. 4305948.665

---